


# C15 ACERT

## ENGINE



### Specifications

**China Stage III Nonroad, U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent**

Engine Configuration . . .	In-Line 6, Diesel
Bore x Stroke . . . . .	137.2 x 171.4 mm (5.4 x 6.75 in)
Displacement . . . . .	15.2 liters (927.56 in <sup>3</sup> )
Ship Weight . . . . .	1469 kg (3239 lbs)

#### Approximate Dimensions:

Length . . . . .	1377 mm (54.2 in)
Width . . . . .	926 mm (36.5 in)
Height . . . . .	1226 mm (48.3 in)

### China Stage III Nonroad, U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent Ratings

TA (ATAAC)	A Rating (Continuous)			B Rating			C Rating (Intermittent)		
	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm
	328	440	1800-2100	354	475	1800-2100	403	540	1800-2100

### U.S. EPA Tier 2 Equivalent, EU Stage II Equivalent Ratings\*\*

TA (ATAAC)	D Rating			D Rating		
	bkW	bhp	rpm	bkW	bhp	rpm
433	580	1800-2100	444	595	1800-2100	

Designed to meet China Stage III Nonroad emission standards. U.S. EPA Tier 3 Nonroad equivalent emission standards (not currently EPA Certified). EU Stage IIIA Nonroad equivalent emission standards (non-current for EU). Available for other regulated and non-regulated areas.