


# G3400

## GAS ENGINES

G3408



### Specifications

	<b>G3406 (TA)</b>	<b>G3408C LE</b>	<b>G3412C LE</b>
<b>Bore x Stroke</b> . . . . .	137 x 165 mm . . . . . (5.4 x 6.5 in)	137 x 152 mm . . . . . (5.4 x 6.0 in)	137 x 152 mm (5.4 x 6.0 in)
<b>Displacement</b> . . . . .	14 liters (893 in <sup>3</sup> ) . . . . .	18 liters (1099 in <sup>3</sup> ) . . . . .	27 liters (1649 in <sup>3</sup> )
<b>Ship Weight</b> . . . . .	1362 kg (3000 lbs) . . . . .	2245 kg (4950 lbs) . . . . .	2141 kg (4720 lbs)
<b>Approximate Dimensions:</b>			
<b>Length</b> . . . . .	1934 mm (76 in) . . . . .	1756 mm (69.1 in) . . . . .	2442 mm (96 in)
<b>Width</b> . . . . .	1270 mm (50 in) . . . . .	1563 mm (61.5 in) . . . . .	1598 mm (63 in)
<b>Height</b> . . . . .	1433 mm (56 in) . . . . .	1758 mm (69.2 in) . . . . .	1960 mm (77 in)

### G3406 Ratings

Engine — Continuous	1800 rpm	
	bkW	bhp
<b>G3406 NA</b> <sup>2</sup>	160	215
<b>G3406 TA</b> <sup>1,2</sup>	206	276
<b>G3406 TA</b> <sup>1,3</sup>	242	325

### G3408 Ratings

Engine — Continuous	1800 rpm	
	bkW	bhp
<b>G3408 NA</b> <sup>2</sup>	190	255
<b>G3408 TA</b> <sup>1,3</sup>	298	400
<b>G3408C LE</b> <sup>1,3</sup>	317	425

### G3412 Ratings

Engine — Continuous	1800 rpm	
	bkW	bhp
<b>G3412 TA</b> <sup>1,3</sup>	448	600
<b>G3412C LE</b> <sup>1</sup>	475	637

<sup>1</sup>54°C/130°F Water to Aftercooler

<sup>2</sup>With customer-supplied air fuel ratio control and aftertreatment

<sup>3</sup>Rating for export only. Not NSPS site compliant capable.

Ratings listed are for 25°C (77°F) ambient temperature, 500 ft. altitude, and pipeline quality gas.

Emission standards: Ratings are NSPS site compliant capable with customer-supplied aftertreatment. Some ratings also have standard emission settings available for export only. For specific emission information please refer to engine spec sheet.